




CF-689

## Automatic Shirt Button Sewing Indexer 自动衬衫钉钮机




- 适用于男女装衬衫钮子筒自动钉钮
- 适合二孔钮和四孔钮，可手动调节布夹距离，钉钮数量可根据
- 需要选择可根据钮子宽窄手动调校钮边距离
- 采用先进送钮装置，配合自动裁片送料系统，大大提高工作效率
- 备自动侧面收料系统能整齐收料，方便操作
- 一人操作两台机产量：3300~3600件/8小时（6粒钮/件）
- 手动调节钉钮范围：320~620mm
- 手动调节钮扣中心与钮子边距离：5~19mm



效果图 Finished Result

|                                                                       |      |
|-----------------------------------------------------------------------|------|
| 缝线Number of threads(根Thread):                                         | 8-8  |
| 钮距 Button spacing(mm):                                                | 85   |
| 车速 Speed(RPM):                                                        | 2200 |
| 车缝长度 Sewing length (mm):                                              | 510  |
| 单台产量 One m/c output(pcs/hr):<br>(6粒钮buttons/件piece, 4孔钮4-hole button) | 225  |

手动调节钮扣中心与钮子边距离：5~19mm  
Manual adjustment of button center to placket edge distance: 5~19mm手动调节钉钮范围：320~620mm  
Manual adjustment of button sewing range: 320~620mm

- Suitable for automatic button sewing on under placket of men or women's shirt
- Suitable for 2- and 4-hole buttons sewing, manual adjustment of distance between fabric clips; button sewing quantity can be preset
- The distance from button to under placket edge can be manually adjusted according to placket width
- Adopt high-precision button feeding device and automatic fabric pieces feeding system to boost efficiency
- Full loading automatic & synchronous feeding system minimizes the influence of fabric friction and static electricity, ensuring feeding stability
- Equipped with automatic collecting system to boost efficiency
- Output by one worker operating two machines: 2400 pcs/8 hours (6 buttons/piece)
- Manual adjustment of button sewing range: 320~620mm
- Manual adjustment of distance between button center and placket edge: 5~19mm

|                                                                                      |                                                                                                                                                                             |
|--------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 型号: CF-689                                                                           | Model: CF-689                                                                                                                                                               |
| 通用缝纫机机型: Juki LK-1903C                                                               | Applicable Sewing Machine Head Model: Juki LK-1903C                                                                                                                         |
| 电源 Power Supply: 1PH/220V/50Hz                                                       | Power Supply: 1PH/220V/50Hz                                                                                                                                                 |
| 总功率 (Kw): 1.5                                                                        | Total Power (Kw): 1.5                                                                                                                                                       |
| 钮扣直径 (mm): 9-20                                                                      | Button Diameter (mm): 9-20                                                                                                                                                  |
| 钮扣厚度 (mm): 1.8-4                                                                     | Button Thickness (mm): 1.8-4                                                                                                                                                |
| 钮扣范围 (mm): 320-620                                                                   | Button Sewing Range (mm): 320-620                                                                                                                                           |
| 钮扣至钮子边距离 (mm): 5-19                                                                  | Distance from Button Center to Placket Edge (mm): 5-19                                                                                                                      |
| 压缩空气压力 (kgf/cm <sup>2</sup> ): 5                                                     | Compressed Air Pressure (kgf/cm <sup>2</sup> ): 5                                                                                                                           |
| 耗压缩空气量 (L/min): 180                                                                  | Compressed Air Consumption (L/min): 180                                                                                                                                     |
| 最大转速 (RPM): 2000-2200                                                                | Max Speed (RPM): 2000-2200                                                                                                                                                  |
| 产能效率 (Per Hour):<br>1人1机: 2100~2300 片/8小时 (6个直眼/片)<br>1人2机: 3300~3600 片/8小时 (6个直眼/片) | Production Capacity (Per Hour):<br>one worker one machines: 2100~2300 pcs/8 hours (6 buttonholes/piece)<br>one worker two machines: 3300~3600 pcs/8 hours (6 buttons/piece) |
| 装箱尺寸【长*宽*高】(m): 2.34×1.08×1.47                                                       | Packing Size 【L*W*H】 (m): 2.34×1.08×1.47                                                                                                                                    |
| 含木箱重量 (KG): 537                                                                      | Gross Weight (KG): 537                                                                                                                                                      |

图片和参数仅供参考，产品规格和外观的修改，恕不另行通知  
Image and parameter for reference only. Product specification and appearance may be modified without notice.