



CF-81

Automatic Collar Trimming Truning and Blocking Machine

自动切领咀反领焗领机



- 适用于切领咀、反领、焗领功能
- 采用PLC控制器控制及人性化操作界面触摸屏操作
- 采用电加热及独立数字温度控制器控制温度
- 下模有定位顶针选择开关，以满足不同布料需求
- 具有特长的压领模
- 采用机械夹固定领，左边机械手辅助收料，减少人工操作
- 生产效率，每8小时产量可达1800~2000条领
- 已安装跟机切刀：C33-00117-3-V1 88° 中间刀




切领咀、反领操作
Collar tip trimming and turning



机械夹夹紧领
Automatic clamp fixing collar



机械夹自动收料
Automatic stacking clamp



• Max pressing length
压领最长：8 1/2 inch

- Suitable for collar tip trimming, turning and blocking
- Adopt PLC and human friendly touch screen for operation
- Electric heated design with independent digital thermostat for temperature control
- Lower mould has selector switch for ejector pin to cater for the requirement of different fabrics
- Ultra long collar pressing mould
- With automatic clamp to fix collar and manipulator on the left side to collect material, it can reduce a lot manual operation
- High production efficiency: it could finish 1800 to 2000pcs of collars every 8 hours
- Installed standard cutter: C33-00117-3-V1 88° cutter

型号: CF-81	Model: CF-81
电源 Power Supply: 1PH/220V/50Hz	Power Supply: 1PH/220V/50Hz
总功率 (Kw): 2.8	Total Power (Kw): 2.8
压领最长尺寸: 8 1/2	Max. Pressing Length (inch): 8 1/2
平均粘合压力 (kgf/cm ²): 5	Average Fusing Pressure (kgf/cm ²): 5
最高温度 (° C): 200	Max Temp. (° C): 200
压缩空气压力 (kgf/cm ²): 5	Compressed Air Pressure (kgf/cm ²): 5
耗压缩空气量 (L/min): 30	Compressed Air Consumption (L/min): 30
产能效率 (Per Hour): 180-360条领/小时	Production Capacity (Per Hour): 180-360Collar/H
装箱尺寸【长*宽*高】(m): 1.08×0.93×1.47	Packing Size【L*W*H】(m): 1.08×0.93×1.47
含木箱重量 (KG): 243	Gross Weight (KG): 243

图片和参数仅供参考，产品规格和外观的修改，恕不另行通知