



CF-85

Automatic Cuff Blocking Machine

自动焗袖口机




- 适合衬衫袖口压烫，使面线更容易
- 采用PLC可编程控制器控制及人性化操作界面触摸显示屏操作
- 只有下模发热，可成型及压平袖口
- 上料模采用底夹
- 备吹风功能，辅助收料，提高工作效率
- 平均产量每8小时达到2400件



自动底夹，防止操作时袖口移位
Automatic bottom clamp for avoiding cuff shift



吹风自动收料
Air blowing facilitates automatic cuff collection



Standard template: Min. width 9 1/4", Max width 12 1/4"


Optional small template: Min. width 6 1/4", Max width 9 1/4"

Optional large template: Min. width 11 1/4", Max width 14 1/4"

跟机标准模 最小尺寸9 1/4"，最大尺寸12 1/4"

选购特造小模最小尺寸6 1/4"，最大尺寸9 1/4"

选购特造大模，最小尺寸11 1/4"，最大尺寸14 1/4"



- Suits for pressing shirt cuff prior to cuff topstitching
- Adopt PLC and user friendly touch screen for operation
- Only the lower mould has heater; it can shape and press cuff;
- Cuff template with bottom clamp
- With air blowing function to assist cuff collection and boost production efficiency
- Average output: 2400 pcs/8hrs

型号: CF-85	Model: CF-85
电源 Power Supply: 1PH/220V/50Hz	Power Supply: 1PH/220V/50Hz
总功率 (Kw): 2	Total Power (Kw): 2
平均粘合压力 (kgf/cm ²): 5	Average Fusing Pressure (kgf/cm ²): 5
最高温度 (° C): 200	Max Temp. (° C): 200
压缩空气压力 (kgf/cm ²): 5	Compressed Air Pressure (kgf/cm ²): 5
耗压缩空气量 (L/min): 30	Compressed Air Consumption (L/min): 30
产能效率 (Per Hour): 360-720个介英/小时 2300-4600个介英/8小时	Production Capacity (Per Hour): 360-720Cuff/H 2300-4600Cuff/8H
装箱尺寸 【长*宽*高】 (m): 0.87×0.87×1.48	Packing Size 【L*W*H】 (m): 0.87×0.87×1.48
含木箱重量 (KG): 180	Gross Weight (KG): 180

图片和参数仅供参考，产品规格和外形的修改，恕不另行通知
Image and parameter are for reference only. Product specification and appearance may be modified without prior notice