




CF-2198/3150

Automatic Triple-buck Fusing Press

自动冷热三头粘合压平机（液压增压系统）



压前模 Press-plate



压后模 Press-plate



液压增压系统 Pressure boosting system

液压、增压缸二次增压，独特压力设计，适合复杂的衬衫面料粘合定型
Hydraulic, secondary pressurization by a booster cylinder, unique pressure design, suitable for complex shirt fabric bonding and shaping

1. 适用于衬衫领、明筒的粘合压烫
2. 采用PLC可编程控制器控制及人性化操作界面触摸屏操作，可设定轻压、重压等压烫方式
3. 上模采用优质铝合金制造，传热速度快且平均；并配合四个数字式温度控制器控制温度更为精确
4. 下模采用伺服马达驱动旋转，旋转定位更精确
5. 双旋转设计，可同时进行压烫、定型、摆料操作，大大提高工作效率
6. 采用冷水机冷却压烫后的衣料，保证最佳压烫效果
7. 优化设计，采用增压缸加压重压，加压压力大，生产效率高，质量好，操作简单，维修方便

1. Suitable for the adhesive pressing of shirt collar and exposed tube
2. PLC programmable controller control and humanized operation interface touch screen operation can be used to set light pressing, heavy pressing and other pressing methods
3. The upper mold is made of high-quality aluminum alloy, with fast and average heat transfer speed. It is more accurate to control temperature with four digital temperature controllers
4. The lower mold is driven by a servo motor, which makes the rotation and positioning more accurate
5. Equipped with 3 moulds rotary design to apply for pressing, cooling and laying material simultaneously, thus the work efficiency has been improved greatly
6. Use a water cooler to cool the pressed clothes to ensure excellent ironing effect
7. Optimized design, pressurization (heavy pressure) with supercharging cylinder, high pressure, high production efficiency, good quality, simple operation and convenient maintenance
8. Prepare high-sensitivity electric eye system to improve operator safety

型号 Model	Model: CF-2198/3150
电源 Power Supply	Power Supply: 3PH/380V/50Hz
总功率 (Kw): 13.4	Total Power (Kw): 13.4
工作台面尺寸 (mm): 400x800/500x1000	Working Table Size (mm): 400x800/500x1000
加压方式: 液压缸增压	Pressure Increasing Mode: By Pressure Booster
平均粘合压力 (kgf/cm ²): 5	Average Fusing Pressure (kgf/cm ²): 5
最高温度 (°C): 200	Max Temp. (°C): 200
压缩空气压力 (kgf/cm ²): 5	Compressed Air Pressure (kgf/cm ²): 5
耗压缩空气量 (L/min): 200	Compressed Air Consumption (L/min): 200
产能效率 (Per Hour): 1500-4200片/时	Production Capacity (Per Hour): 1500-4200 Pcs/Hr
装箱尺寸【长*宽*高】(mm): 2.51x2.40x1.78	Packing Size 【L*W*H】 (mm): 2.51x2.40x1.78
毛重 (KG): 1350	Gross Weight (KG): 1350