



# CF-350

Rotary Pressing Machine

轆熨机



- 适用于折迭和压烫三类侧
- 自动运输带平衡系统，滚筒式运输带设计，操作简单
- 压力可调，可选购安装各种侧翼制作不同风格的三类侧
- 采用优质红外线恒温针，温度控制精确，折烫效果佳
- 操作空间大，可容纳两人同时作业，以提高产量
- 工作宽度: 800mm
- 最高设计温度: 200℃

## 選購件-Options



P537三角侧翼侧翼  
Plait Folder



P538三角侧翼侧翼  
Triangular Sleeve Placket Folder



P539矩形侧翼侧翼  
Rectangular Sleeve Placket Folder




P540三角侧翼侧翼  
Triangular Sleeve Placket Folder



P541三角侧翼侧翼  
Triangular Sleeve Placket Folder



P543矩形侧翼侧翼  
Plait Folder



- Suitable for folding and pressing triangular sleeve placket
- Automatic conveyor belt balance system, roller conveyor belt design, easy operation
- Adjustable pressing force; various optional folders can be mounted to produce sleeve plackets of different styles
- With high-quality infrared thermostat sensor, accurate temperature control and superb folding and pressing effect
- Large operating space allows two workers to operate simultaneously, thereby to double the output
- Working width: 800mm
- Max. temperature: 200℃

|                                  |                                                   |
|----------------------------------|---------------------------------------------------|
| 型号: CF-350                       | Model: CF-350                                     |
| 电源 Power Supply: 1PH/220V/50Hz   | Power Supply: 1PH/220V/50Hz                       |
| 总功率 (Kw): 3.2                    | Total Power (Kw): 3.2                             |
| 最高温度 (° C): 200                  | Max Temp. (° C): 200                              |
| 压缩空气压力 (kgf/cm <sup>2</sup> ): 5 | Compressed Air Pressure (kgf/cm <sup>2</sup> ): 5 |
| 耗压缩空气量 (L/min): 40               | Compressed Air Consumption (L/min): 40            |
| 产能效率 (Per Hour): 200对/小时         | Production Capacity (Per Hour): 200Pairs/H        |
| 装箱尺寸 【长*宽*高】 (m): 1.25x0.71x0.61 | Packing Size 【L*W*H】 (m): 1.25x0.71x0.61          |
| 含木箱重量 (KG): 350                  | Gross Weight (KG): 350                            |

图片和参数仅供参考，产品规格和外貌的修改，恕不另行通知  
Images and parameters for reference only. Product specifications and appearance may be modified without prior notice